

STANDARD PAVEMENT SECTION

- 6" CLASS B ASPHALT (2 LIFTS)
- 6" ATB (2 LIFTS)
- 3" CRUSHED SURFACING TOP COURSE

ALTERNATE PAVEMENT SECTION

- 6" CLASS B ASPHALT (2 LIFTS)
- 8" CRUSHED SURFACING TOP COURSE
- CRUSHED SURFACING BASE COURSE, THICKNESS DETERMINED BY DESIGN


CONSTRUCTION NOTES:

1. PAVEMENT SECTIONS SHALL BE PLACED OVER 12" MINIMUM COMPACTED SUBGRADE (95% MDD).
2. PAVEMENT SECTION DEPTHS NOTED REFER TO COMPACTED DEPTH.
3. SLOPE EASEMENTS MAY BE REQUIRED FOR GRADING OUTSIDE DEDICATED RIGHT-OF-WAY.
4. PLANTER STRIP SHALL DRAIN TOWARD STREET AT 0 TO 10% CROSS-SLOPE.
5. ADDITIONAL RIGHT-OF-WAY MAY BE REQUIRED FOR U-TURN LANE AT INTERSECTIONS.
6. NO PARKING ON ARTERIALS.

- ① CONCRETE CURB AND GUTTER (TYPE A-1) PER STANDARD DETAIL 323. FLOWLINE ELEV = CL - 0.76' & TOP OF CURB ELEV = CL - 0.26'
- ② CONCRETE SIDEWALK PER STANDARD DETAIL 306. BACK OF WALK ELEV = CL + 0.00' (TYP)



City of Covington
Public Works
Community Development



**TYPICAL STREET SECTION
MINOR ARTERIAL**

This document has been signed electronically in accordance with WAC 196-23-070 and Chapter 19.34 RCW. Unauthorized alteration of any of the information on this document will invalidate the document, my certification and signature.

203

Revision Date
July 2009