

**CONSTRUCTION NOTES:**


1. PAVEMENT SECTIONS SHALL BE PLACED OVER 12" MINIMUM COMPACTED SUBGRADE (95% MDD).
2. PAVEMENT SECTION DEPTHS NOTED REFER TO COMPACTED DEPTH.
3. SLOPE EASEMENTS MAY BE REQUIRED FOR GRADING OUTSIDE DEDICATED RIGHT-OF-WAY.
4. PLANTER STRIP SHALL DRAIN TOWARD STREET AT 0 TO 10% CROSS-SLOPE.
5. NO PARKING ON ARTERIALS.

① CONCRETE CURB AND GUTTER (TYPE A-1) PER STANDARD DETAIL 323.  
FLOWLINE ELEV = CL - 0.54' & TOP OF CURB ELEV = CL - 0.04'

② CONCRETE SIDEWALK PER STANDARD DETAIL 306.  
BACK OF WALK ELEV = CL + 0.22' (TYP)



**City of Covington**  
Public Works  
Community Development



**TYPICAL STREET SECTION  
COLLECTOR ARTERIAL**

This document has been signed electronically in accordance with WAC 196-23-070 and Chapter 19.34 RCW. Unauthorized alteration of any of the information on this document will invalidate the document, my certification and signature.

**204**

Revision Date  
July 2009