

CONSTRUCTION NOTES:


1. PAVEMENT SECTIONS SHALL BE PLACED OVER 12" MINIMUM COMPACTED SUBGRADE (95% MDD).
2. PAVEMENT SECTION DEPTHS NOTED REFER TO COMPACTED DEPTH.
3. SLOPE EASEMENTS MAY BE REQUIRED FOR GRADING OUTSIDE DEDICATED RIGHT-OF-WAY.
4. PLANTER STRIP SHALL DRAIN TOWARD STREET AT 0 TO 10% CROSS-SLOPE.
5. CHANNELIZATION MAY INCLUDE BIKE LANES, TURN LANES AND/OR PARKING LANES.
6. ADDITIONAL RIGHT-OF-WAY MAY BE REQUIRED FOR BIKE LANES, TURN LANES AND/OR PARKING LANES.
7. ADDITIONAL OR ALTERNATE STANDARDS MAY BE REQUIRED WITHIN THE DOWNTOWN ZONE.

① CONCRETE CURB AND GUTTER (TYPE A-1) PER STANDARD DETAIL 323.
FLOWLINE ELEV = CL - 0.54' & TOP OF CURB ELEV = CL - 0.04'

② CONCRETE SIDEWALK PER STANDARD DETAIL 306.
BACK OF WALK ELEV = CL + 0.22' (TYP)



City of Covington
Public Works
Community Development



**TYPICAL STREET SECTION
COMMERCIAL / INDUSTRIAL**

This document has been signed electronically in accordance with WAC 196-23-070 and Chapter 19.34 RCW. Unauthorized alteration of any of the information on this document will invalidate the document, my certification and signature.

205

Revision Date
July 2009