


CONSTRUCTION NOTES:

1. PAVEMENT SECTIONS SHALL BE PLACED OVER 12" MINIMUM COMPACTED SUBGRADE (95% MDD).
2. PAVEMENT SECTION DEPTHS NOTED REFER TO COMPACTED DEPTH.
3. SLOPE EASEMENTS MAY BE REQUIRED FOR GRADING OUTSIDE DEDICATED RIGHT-OF-WAY.
4. PLANTER STRIP SHALL DRAIN TOWARD STREET AT 0 TO 10% CROSS-SLOPE.
5. ADDITIONAL RIGHT-OF-WAY MAY BE REQUIRED FOR BIKE LANES, TURN LANES AND/OR PARKING LANES.

- ① CONCRETE CURB AND GUTTER (TYPE A-1) PER STANDARD DETAIL 323.
FLOWLINE ELEV = CL - 0.42' & TOP OF CURB ELEV = CL + 0.08'
- ② CONCRETE SIDEWALK PER STANDARD DETAIL 306.
BACK OF WALK ELEV = CL + 0.28' (TYP)

	<p>City of Covington</p> <hr/> <p>Public Works</p> <hr/> <p>Community Development</p>		<p>TYPICAL STREET SECTION</p> <p>NEIGHBORHOOD COLLECTOR</p>	<p>206</p>
<p>This document has been signed electronically in accordance with WAC 196-23-070 and Chapter 19.34 RCW. Unauthorized alteration of any of the information on this document will invalidate the document, my certification and signature.</p>				<p>Revision Date July 2009</p>