


DETAIL NOTES

See plans and/or specifications for size, type of pipe, elevations and orifice specifications.

Restrictor riser shall be constructed of corrugated polyethylene pipe (AASHTO M294 Type S), polyvinyl chloride (PVC – AASHTO D-3034 Schedule 40) or aluminized CMP.

For PVC applications, all connections shall be made using standard fittings. No welding.

- ① FOR HDPE APPLICATIONS
3/8" HDPE PLATE WELDED ALL AROUND – ORIFICE OPENING SIZE ACCORDING TO PLANS.
- ② OUTLET PIPE MAY BE ADS N12 SMOOTH HDPE OR TAPERED SMOOTH HDPE – TYPE, LENGTH AND SIZE AS SHOWN ON PLANS.

 <p>City of Covington Public Works Community Development</p>	 <p>RESTRICTOR RISER</p>	<p>This document has been signed electronically in accordance with WAC 196-23-070 and Chapter 19.34 RCW. Unauthorized alteration of any of the information on this document will invalidate the document, my certification and signature.</p>		
		<table border="1" style="width: 100%;"> <tr> <td style="text-align: center; font-size: 2em; font-weight: bold;">746</td> </tr> <tr> <td style="text-align: center;">Revision Date January 2010</td> </tr> </table>	746	Revision Date January 2010
746				
Revision Date January 2010				