

STANDARD PAVEMENT SECTION

- 6" CLASS B ASPHALT (2 LIFTS)
- 6" ATB (2 LIFTS)
- 3" CRUSHED SURFACING TOP COURSE

ALTERNATE PAVEMENT SECTION

- 6" CLASS B ASPHALT (2 LIFTS)
- 8" CRUSHED SURFACING TOP COURSE
- CRUSHED SURFACING BASE COURSE, THICKNESS DETERMINED BY DESIGN


CONSTRUCTION NOTES:

1. PAVEMENT SECTIONS SHALL BE PLACED OVER 12" MINIMUM COMPACTED SUBGRADE (95% MDD).
2. PAVEMENT SECTION DEPTHS NOTED REFER TO COMPACTED DEPTH.
3. SLOPE EASEMENTS MAY BE REQUIRED FOR GRADING OUTSIDE DEDICATED RIGHT-OF-WAY.
4. PLANTER STRIP SHALL DRAIN TOWARD STREET AT 0 TO 10% CROSS-SLOPE.
5. NO PARKING ON ARTERIALS.

- ① CONCRETE CURB AND GUTTER (TYPE A-1) PER STANDARD DETAIL 323.
FLOWLINE ELEV = CL - 1.00' & TOP OF CURB ELEV = CL - 0.50'
- ② CONCRETE SIDEWALK PER STANDARD DETAIL 306.
BACK OF WALK ELEV = CL - 0.20' (TYP)
- ③ CONCRETE CURB (TYPE E-4) PER STANDARD DETAIL 324, WHERE APPLICABLE.
TOP OF CURB ELEV = CL + 0.34'



City of Covington
Public Works
Community Development



**TYPICAL STREET SECTION
PRINCIPAL ARTERIAL**

This document has been signed electronically in accordance with WAC 196-23-070 and Chapter 19.34 RCW. Unauthorized alteration of any of the information on this document will invalidate the document, my certification and signature.

202

Revision Date
July 2009